

# D

## Reciprocating High Pressure Air Compressors



1,5-11 kW

**DALGAKIRAN**



145-1766  
l/min

1,5-11  
kW

7-12,5  
bar



## D SERIES

*Single & Double Stage, Belt Driven  
Reciprocating Air Compressors*

Reliable, Long-Lasting, and Durable: Preferred by Many Industries for its Versatility



### General Features

- Reliable design
- Safe to use
- High-quality components and safety systems
- Energy efficient



### Advantages

- Offers ideal solutions for small business enterprises.
- Service-friendly design reduces maintenance costs.
- Produces reliable and efficient pressure.
- Uses quality components for a long service life.
- Low noise levels.





## Safety System

- Safe operation with pressure switch, check valve and safety valve
- Belt-pulley guard
- Manometer
- Ready-to-run electrical mechanism



## Compressor Block

- Cast cylinder body
- Aluminium injection-moulded cylinder head
- Special aluminium alloy pistons and connecting rod
- Cast pulley for fan-type efficient cooling
- Splash lubrication
- Oil level gauge
- Factory-filled oil
- Star/delta connectors (5.5 kW and above)
- External panel (optiona



## Air Tank

- Designed in compliance with CE rules
- P235GH / P265GH steel
- Manuel drainage valve
- Air outlet valve
- Impact-resistant electrostatic powder coating



## Certification

- Designed in compliance with CE rules; air tanks made with P235GH / P265GH standard steel

Model	Working Pressure	Piston Displacement	Motor Power	Air Connection	Dimensions (mm)			Weight	Air Receiver
	bar	l/min	kW / HP		Length	Width	Height	kg	l
<b>SINGLE STAGE</b>									
<b>D 2-100 D</b>	7	178	1,5/2	2 x G¼"	450	1100	820	81	100
<b>D 3-200 D</b>	7	290	2,2/3	2 x G¼"	450	1445	965	127	200
<b>D 4-300</b>	7	501	3/4	1 x G¼" + 1 x G¾"	450	1745	1000	147	250
<b>D 5,5-300</b>	7	649	4/5,5	2 x G¼" + 1 x G¾"	450	1745	1030	180	250
<b>D 5,5-500</b>	7	649	4/5,5	2 x G¼" + 1 x G¾"	640	1915	1260	264	500
<b>D 7,5-500</b>	7	971	5,5/7,5	2 x G¼" + 1 x G¾"	640	1915	1350	283	500
<b>D 10-500</b>	7	1222	7,5/10	2 x G¼" + 1 x G¾"	640	1915	1370	297	500
<b>D 15-500</b>	7	1766	11/15	2 x G¼" + 1 x G¾"	700	1840	1520	465	500
<b>DOUBLE STAGE</b>									
<b>D 3-200 MT</b>	12,5	145	2,2/3	2 x G¼"	450	1445	965	132	200
<b>D 4-300 T</b>	12,5	334	3/4	1 x G¼" + 1 x G¾"	450	1755	1000	167	250
<b>D 5,5-300 T</b>	12,5	324	4/5,5	2 x G¼" + 1 x G¾"	450	1755	1030	198	250
<b>D 5,5-500 T</b>	12,5	324	4/5,5	2 x G¼" + 1 x G¾"	640	1910	1255	330	500
<b>D 7,5-500 T</b>	12,5	647	5,5/7,5	2 x G¼" + 1 x G¾"	640	1910	1275	350	500
<b>D 10-500</b>	12,5	726	7,5/10	2 x G¼" + 1 x G¾"	700	1910	1355	365	500

- Dalgakiran reserves its rights to make changes in its products and specifications without prior notice.