



100-10000
L

Vertical

10-40
bar

AIR
RECEIVER

JOURNEY
OF
AIR

Air tanks are used for storage in compressed air systems. They prevent pressure fluctuations in the system and eliminate inefficiencies especially in fix speed compressor applications.

Advantages

- They allow the system to respond quickly to high and sudden consumption
- A key component of compressed air systems
- Storage function
- Reduces system pressure fluctuations
- Increases efficiency
- Galvanized and stainless steel options
- Energy saving
- Highly durable with a long service life

Model	Volume	Pressure	Configuration	Dimensions (mm)		Connection Inlet / Outlet
	L	bar		Diameter	Height	
DHT 100	100	10	VERTICAL	324	1564	G 1"
		15	VERTICAL	324	1564	G 1"
DHT 200	200	10	VERTICAL	450	1618	G 1"
		15	VERTICAL	450	1618	G 1"
DHT 300	300	10	VERTICAL	450	1918	G ¾"
		16,5	VERTICAL	500	1960	G 1"
		40	VERTICAL	450	2012	G 1"
DHT 500	500	10	VERTICAL	642	1980	G 1"
		17	VERTICAL	642	2115	G 1"
		40	VERTICAL	642	2083	G 1 ¼"
DHT 900	900	10	VERTICAL	800	2120	G 1 ½"
DHT 1000	1000	10	VERTICAL	850	2120	G 1 ½"
		17	VERTICAL	850	2292	G 1 ½"
		40	VERTICAL	850	2120	G 1 ½"
DHT 1800	1800	10	VERTICAL	1150	2150	G 2"
		15	VERTICAL	1150	2150	G 2"
DHT 2000	2000	10	VERTICAL	1080	2566	G 2"
		15	VERTICAL	1080	2566	G 2"
		15	VERTICAL	1150	2240	G 2"
DHT 3000	3000	10	VERTICAL	1400	2370	G 2 ½"
		15	VERTICAL	1400	2370	G 2 ½"
DHT 4000	4000	10	VERTICAL	1400	3120	G 3"
		15	VERTICAL	1400	3120	G 3"
DHT 5000	5000	10	VERTICAL	1400	3870	G 3"
		15	VERTICAL	1400	3870	G 3"
DHT 6000	6000	10	VERTICAL	1500	3930	G 3"
		15	VERTICAL	1500	3930	G 3"
DHT 8000	8000	10	VERTICAL	1750	4040	DN100
		15	VERTICAL	1750	4040	DN100
DHT 10000	10000	10	VERTICAL	1900	4100	DN100
		15	VERTICAL	1900	4100	DN100